

Mira Matte

Natural Stone Color Enhancer



www.miraclesealants.com

Color Enhancement For Textured Surfaces Including:

- Flamed Granite
- Flamed Limestone
- Textured Cast Stone
- Cleft Faced Slate
- Tumbled Marble
- Textured Natural Stone

Special Features

- Interior & Exterior
- Water Resistant
- U. V. Transparent
- Easy To Use
- Stain Resistant
- Non yellowing

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. Mira Matte is a unique product designed to enhance the natural color of all flamed, sandblasted, split faced, tumbled and textured surfaces. When used with one of our **Miracle Penetrating Sealers**, Mira Matte seals and protects while leaving a beautiful, low maintenance, color enhanced satin sheen. Mira Matte allows vapor to escape while offering a scuff and weather resistant surface. Mira Matte is U.V. transparent, will not yellow and can be used on both interior and exterior applications.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.

Polish Enhancement

Not recommended.

NEW INSTALLATIONS - APPLICATION INSTRUCTIONS

Read entire label and PDS/MSDS before using. Mira Matte should not be diluted or thinned in any way. Mira Matte should be used as is direct from approved container.

Before Grouting: Apply **Miracle Penetrating Sealer** to all surfaces. This step will allow quick and easy cleanup after grouting. Grout can stain many surfaces if this procedure is not used. Apply **Miracle Penetrating Sealer** using a **Mira Brush Applicator** or a clean white towel. Apply enough to wet the surface. Be careful not to saturate the open grout joints. Allow **Miracle Penetrating Sealer** to stand for approximately 1 - 5 minutes for maximum penetration. Any excess sealer remaining at this time should be removed by wiping the surface with a clean dry towel. Typically we do not recommend a second application of sealer when utilizing **Mira Matte**. Allow **Miracle Penetrating Sealer** to dry 6 - 12 hours before continuing with the grouting procedure per manufacturers specification.

After Grouting: Once grouted make sure that all grout residue is removed from the surface with a clean sponge and water. Allow grout joints to dry at least 24 hours. If grout clean up is not performed effectively, additional cleaning may be necessary to remove remaining grout residue or haze. For this procedure use **HDAC (Heavy Duty Acidic Cleaner)**, **Phosphoric Acid Cleaner** or **Epoxy Grout Film Remover** as directed. Once the area has completely dried, proceed with the sealing of the grout for water and stain resistance. Apply **Miracle Penetrating Sealer** to all grout as directed. Allow sealer to dry a minimum of 1 hour. Apply **Mira Matte** to the entire surface using a natural fiber brush, terry cloth towel or pump sprayer (exterior use only). If a pump sprayer is used, **Mira Matte** should be evened out with a brush before it dries. Work small areas 30 - 60 square feet (3 - 6 square meters) at a time. Do not allow **Mira Matte** to puddle on the surface. Multiple applications may be necessary to achieve the desired results. Proceed with subsequent applications after the previous application has dried to the touch (approximately 1 - 2 hours). Be sure to even out **Mira Matte** on the surface, blending in overlap marks.

Existing Installations - Surface Preparations

Surface must be dry and free of contaminant, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust & other heavy dirt and grime.

Surface Coating/Wax Removal: To remove existing coatings and/or waxes, use **Mira Strip** or **Finish Sealer Stripper** per the instructions.

Heavy Duty Cleaning: To remove lime, hard water deposits, efflorescence, rust and other heavy dirt and grime use **HDAC** or **Phosphoric Acid Cleaner** as directed. If an additional non acid deep cleaning is necessary use **Liquid Poutlice** as directed.

Light Cleaning: Use **Tile & Stone Cleaner**, **Limestone/Travertine Soap** or **Counter Kleen** as directed.

Existing Installations - Application Instructions:

Follow the application instructions previously mentioned, except now, seal the grout joints at the same time as the rest of the tile or stone surface. When treating surface and grout at the same time, make sure all grout joints are saturated with **Miracle Penetrating Sealer**. Once the sealer is dry to the touch (1 - 2 hours), proceed with the application of **Mira Matte** color enhancer as previously mentioned. For added color where maximum stain repellency is not required, use **Mira Matte** by itself.

Cure Time

Mira Matte will be dry to the touch in 2 - 4 hours and may be used for normal foot traffic. For optimum results the area should be kept dry and free from staining materials for 72 hours.

Coverage

Coverage will vary depending on the density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Mira Matte** will cover approximately 50 - 200 square feet per quart (4.5 - 8 square meters per .948 liters).

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide**. Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store **Mira Matte** in the original container, properly sealed to avoid contamination and solvent evaporation. Stored at 77° F (25° C), **Mira Matte** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435
website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

WARRANTY & CAUTIONS

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Mira Matte contains petroleum distillates. All solvents must be considered toxic and must be used in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surfaces has thoroughly dried. **Refer to the MSDS for additional information.**



Safety Data Sheet

Issue Date 01-Feb-2012

Revision Date: 29-Aug-2013

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Mira Matte

Other means of identification

SDS # MSC-012

UN/ID No UN1268

Product Code OMB No. 1218-0072 / Identity No: 6477

Recommended use of the chemical and restrictions on use

Recommended Use Water, Stain & Slip Protection for: Quarry Tile, Ceramic Tile, Porcelain Tile, Glazed Tile, Marble, Granite, Travertine, Slate, Grout, Quartz, Brick, Terrazzo.

Details of the supplier of the safety data sheet

Supplier Address

Miracle Sealants Company
12318 Lower Azusa Road
Arcadia, CA 91006

Emergency Telephone Number

Company Phone Number 1-626-443-6433 (Phone)
1-626-443-1435 (Fax)

24 Hour Emergency Phone Number 1-800-350-1901

Emergency Telephone (24 hr)

For product spills, leaks or exposures call:
Infotrac 1-800-535-5053 (North America) or 1-352-323-3500 (International)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Signal Word

Danger

Hazard Statements

Harmful if swallowed
 Toxic if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause genetic defects
 Suspected of damaging fertility or the unborn child
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor



Appearance Clear, colorless liquid

Physical State Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 If skin irritation persists: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting
 Rinse mouth
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Other Hazards

Toxic to aquatic life with long lasting effects
Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aromatic solvent	64742-95-6	Proprietary
Toluene	108-88-3	Proprietary
2-Butoxyethanol	111-76-2	Proprietary

Product contains a proprietary mixture of ingredients.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Flush with water for 15 minutes. If irritation persists, call physician.
Skin Contact	Wash off with soap and water. If irritation persists, call physician.
Inhalation	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical attention.
Ingestion	Do not induce vomiting. Call physician. Keep victim's head below hips to prevent aspiration.

Most important symptoms and effects

Symptoms	Eyes: Burning sensation. Skin: Irritant. Ingestion: Toxic, do not induce vomiting, call physician. Inhalation: Dizziness, headaches, and irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Medical conditions generally aggravated by exposure- same as signs and symptoms of over exposure.
---------------------------	---

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, or dry foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is flammable.

Hazardous Combustion Products Carbon oxides.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool exposed containers with water to prevent rupturing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective clothing as described in Section 8 of this safety data sheet. Ventilate affected area.

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Steps to be taken in case material is released or spilled: wipe, scrape or soak up in an inert material and put in a container for disposal. Use clean non-sparking tools to collect absorbed material. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of the reach of children. Wash face, hands, and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use only with adequate ventilation. Keep container tightly closed. Ground container and transfer equipment to eliminate static electric sparks. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep cool. Do not breathe vapors or spray mist.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Store in a cool, dry place, out of direct sunlight. Do not freeze, less than or equal to 32°F or heat above 110°F. Keep out of the reach of children. Store locked up.

Incompatible Materials Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
-----------------------------	-------------	--	--

Appropriate engineering controls

Engineering Controls Local exhaust: Recommended
Mechanical exhaust: General ventilation system should be provided.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight fitting, splash proof safety goggles.

Skin and Body Protection Protective gloves: Plastic or rubber, chemical resistant
Protective clothing or equipment: Chemical resistant clothing.

Respiratory Protection Ventilate by opening all doors and windows. If exposure above the TLV or PEL require a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CFR 1910.134 is required.

General Hygiene Considerations Work hygienic practices: Wash hands thoroughly before handling foodstuffs, liquids or tobacco products. Use common sense and care around chemicals. Never mix this product with other chemicals. Consult your supervisor for all other hygienic and safety practices. All practices depend on your specific business. Directions for use normally found on label which will dictate engineering and control measures. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Solvent
Appearance	Clear, colorless liquid	Odor Threshold	Not determined
Color	Colorless		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<u>Method</u>		
pH	Neutral	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	212 °F / 100 °C	
Flash Point	46.66 °C / 116 °F	
Evaporation Rate	Not available	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	
Lower Flammability Limit	Not available	
Vapor Pressure	Not available	
Vapor Density	Not available	
Specific Gravity	0.85	
Water Solubility	insoluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content	738 g/L	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from sources of ignition such as heat, sparks or open flames.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation. May be harmful in contact with skin.

Inhalation Toxic if inhaled.

Ingestion Harmful if swallowed; May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic solvent 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit) = 12124 mg/kg (Rat)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
---------------	-------	------	-----	------

Toluene 108-88-3		Group 3		
2-Butoxyethanol 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Reproductive toxicity Suspected of damaging fertility or the unborn child.**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard** May be fatal if swallowed and enters airways.**Numerical measures of toxicity**

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Aromatic solvent 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50		6.14: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Toluene 108-88-3	2.65

2-Butoxyethanol 111-76-2	0.81
-----------------------------	------

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1268
Proper Shipping Name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III

IATA

UN/ID No UN1268

Proper Shipping Name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III

IMDG

UN/ID No UN1268
Proper Shipping Name Petroleum distillates, n.o.s.
Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	Proprietary	1.0
2-Butoxyethanol - 111-76-2	111-76-2	Proprietary	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

Toluene 108-88-3 (Proprietary)	1000 lb	X	X	X
-------------------------------------	---------	---	---	---

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Toluene 108-88-3	X	X	X
2-Butoxyethanol 111-76-2	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	2	0	None
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	2	0	Not determined

Issue Date 01-Feb-2012
Revision Date: 29-Aug-2013
Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet